Application No.: Not Yet Assigned Docket No.: I0231.0009/P009

JC17 Rec'd PCT/PTO 17 JUN 2005

1. (Currently Amended) System to open/close sheet-formed bodies in particular containers, bags, sacs and the like, made of paper and/or synthetic materials and provided with a closable mouth at one end thereof, said system comprising a clip device consisting of a male element (M) and a female element (F) having at one end thereof a common articulation able to be inserted in an open or uncoupled configuration on a portion or limb of said month mouth, and to lock or seal thereupon assuming a closed or coupled configuration which imprisons said limb portion, characterized by the combination of: - means of articulation acting as a snap-free spring at one of the two ends of said essentially longitudinal elements, formed of continuous protuberances integral with each other and with said elements; - anti-tampering means at the second opposite end of same elements, comprising two small separate tongues each projecting from each element male respectively female; - sealing means resulting from the form-coupling of fixed joints complementary to each other made on/in said (M) and (F) elements; - means to smootly tear cutting made of knurl on the top of one of the flanks of the female element; - possible carrying means to move or transport the container; wherein said multifuntional and highly perfomant clip device is associated to a portion of the container mouth limb, provided with an ad hoc invitation coupling means.

- 2. (Original) System according to claim 1, in which said male element has a solid cylindrical shape whereas the female element has an at least partially hollow shape.
- 3. (Original) System according to claim 1, in which the male element has in cross-section the shape of a partially opened pincers.

Application No.: Not Yet Assigned Docket No.: I0231.0009/P009

4. (Original) System according to claim 1, in which the female element has a cross section in form of a horse shoe with a central male protrusion penetrating into an empty partially opened portion of the male pincers.

- 5. (Currently Amended) System according to at least one of the above claims claim 1, in which the top inner portion of one of the female element flanks is in form of a knurl.
- 6. (Currently Amended) System according to at least one of the above claims <u>claim</u>

 1. in which a handle is on the outer back of the female element.
- 7. (Currently Amended) System according to at least one of the above claims claim 1, in which a reinforcing partial sleeve is on a portion of said female element and has on outer toothed grip.
- 8. (Currently Amended) System according to at least one of the above claims claim 1, in which the clip male element is inserted on a bag mouth invitation coupling means with the aid of pincers, arms and the like whereas the welding of the lips at the ends of the male and female components is carried out by heat-sealing heads, even out of line.
- 9. (Currently Amended) Method to <u>assemble assembly</u>, <u>deassemble de-assembly</u> on/from a container mouth a clip device according to <u>the above claims claim 1</u>, comprising the steps of: providing the container mouth with <u>an invitation a coupling means</u>; providing the female element with a reinforcing sleeve and a handle; opening the clip by separating its male-and female-elements; applying in correspondence of said <u>invitation coupling means</u> the clip device in said opened configuration; inserting the male element into the female element by forcing to a narrow coupling the

Application No.: Not Yet Assigned Docket No.: I0231.0009/P009

penetration of the male element pincers on the central protrusion of the horse shoe shaped female element; - sealing the lips at the free ends of both elements.

10. (Original) Apparatus to automatically apply the clip of <u>claim 1</u> elaims 1—8, on the mouth of a container comprising: - a conveyor of formed and filled bags from a packaging unit; - at least a vibrating- screening container of clips to be fed to a device receiving both said bags and clips and comprising pneumatic pliers to open the male and female elements on arrival of the bags against the clip proximal end; - means to insert said opened clip elements on the bag mouth <u>invitation</u>; and - means to seal the projecting lips.